



PERSONAL
COMPUTERS



SMALL
COMPUTERS
NETWORK

iDialog / iDialog Plus

400-800 VA / 400-1600 VA

single-phase

iDialog / iDialog Plus 400-800 VA / 400-1600 VA



The **iDialog** UPS has been designed to protect PCs and critical peripherals in home and small office environments. iDialog is easy to install and provides powerful, economic protection for:


- IT equipment including PCs, Media Centers, PoE, VoIP and other such peripherals
- TVs, Home Cinemas, Satellite and Digital Terrestrial receivers, DVD readers and writers
- Modems and xDSL routers
- Small household appliances

Particolare dei display



CHARACTERISTICS

- Maximum power protection with **PowerShield³** UPS monitoring and shutdown software available for free download from our website www.riello-ups.com
- Suitable for installation on PC's running Windows Vista, 2003, XP, 2000, Me, 98; Linux, Mac OSX and the Sun Solaris operating system.
- Compact dimensions and ergonomic design: **iDialog** can be placed on a desk top or other convenient location, with easy to access connections and informative front panel.
- Front panel LCD display (**Plus** version only) providing status, load and battery information and LEDs (standard version).



- Silent running: **iDialog** can be used to protect other sensitive electronic devices including Home Cinemas, CD Writers, DVD players, Satellite and Digital Terrestrial receivers.

2 YEAR WARRANTY

| MODELS | ID 40 | ID 60 | ID 80 | IDP 40 | IDP 60 | IDP 80 | IDP 110 | IDP 160 | |
|--------------------------------|--|------------|---------------------------------------|------------|------------|---------------------------------------|---------------|-------------|--|
| POWER | 400VA/240W | 600VA/360W | 800VA/480W | 400VA/240W | 600VA/360W | 800VA/480W | 1100VA/660W | 1600VA/960W | |
| INPUT | | | | | | | | | |
| Rated voltage | 220-240 Vac | | | | | | | | |
| Voltage range | 230 Vac (+20/-25%) | | | | | | | | |
| Frequency | 50/60 Hz auto sensing | | | | | | | | |
| OUTPUT | | | | | | | | | |
| Voltage on mains operation | 230 Vac (+/- 15%) | | | | | | | | |
| Voltage on battery operation | 230 Vac (+/- 10%) | | | | | | | | |
| Frequency on battery operation | 50 or 60 Hz (+/- 1%) | | | | | | | | |
| BATTERIES | | | | | | | | | |
| Type | VRLA AGM Maintenance-free lead-acid | | | | | | | | |
| Recharge time | 6-8 h | | | | | | | | |
| ENVIRONMENTAL | | | | | | | | | |
| Weight (kg) | 3 | | | 3.2 | | 3.4 | 6.6 | 7 | |
| Dimensions (hwd) (mm) | 192 x 90 x 232 | | | | | | 275 x 97x 315 | | |
| Tel/Modem protection | RJ11/45 connectors | | | | | | | | |
| Communication | n.d. | | | USB | | | | | |
| Output sockets | 4 IEC | | 4 IEC or 3 Schuko/Italian or 3 french | | | 6 IEC or 4 Schuko/Italian or 4 french | | | |
| Safety compliance | EN 62040-1-1 and Directives 73/23 EC, 93/68 EC, EN 62040-3 | | | | | | | | |
| EMC conformance | EN 62040-2 and Directives 2004/108 EC, 93/68 EC | | | | | | | | |
| Marks | CE | | | | | | | | |
| Operating temperature | 0°C / +40°C | | | | | | | | |
| Colour | Dark grey | | | | | | | | |
| Altitude and relative humidity | 6000 meters max. elevation, < 95% non condensing | | | | | | | | |
| Accessories provided | 2 output supply cables (IEC version), 1 USB cable (plus version), user guide | | | | | | | | |

